

SPECIFICATIONS FOR ENGLAND'S STOVE WORKS UNITS

(Rev. 11/2004)

NOTE: These specifications, along with stove pictures, data, parts & accessory pricing and other information, can also be found at www.englishstoveworks.com.

This list contains information on both currently-produced and recent older model numbers.

WOOD STOVES

Specifications for 13-NCC, 13-NCP, 13-NCL & 13-NCG; 50-SNC13C, 50-SNC13P, 50-SNC13L, 50-SNC13PL & 50-SNC13G; 50-TNC13C, 50-TNC13P, 50-TNC13L & 50-TNC13G and Golden Eagle Parts

| | |
|--------------------------------|------------------------|
| Dimensions | 25 1/4"W x 26"H x 14"D |
| Weight | 295 lbs. |
| Heating Capacity | App. 1,500 sq. ft. |
| Firebox Size | 1.8 cu. ft. |
| Max. Log Length | 18" |
| Door Opening Size | 16" x 8 1/2" |
| Window Opening | 15 3/4" x 8 1/2" |
| Type of Fuel | Wood |
| Flue Size I.D. | 6" |
| Flue Hgt. to Top Exhaust | 27 1/2" |
| AC-G17 Glass | 9 1/4" x 16 1/2" |
| Ash Drawer | Standard |

Options:

| | |
|----------------|---|
| AC-16 | Room air blower |
| AC-107 | Brass lip trim (AC-107BN if Nickel) |
| AC-108 | Brass trim ring for door (AC-108BN if Nickel) |
| AC-NCSHS | Side heat shield (AC-NCSHSB for black) |
| CA-12G | Gold-plated leg |
| CA-13G | Gold-plated door |

Specifications for 12-FPP, 12-FPL & 12-FPG; 50-SFP12P, 50-SFP12L & 50-SFP12G; 50-TFP12P, 50-TFP12L & 50-TFP12G

| | |
|-------------------------|------------------------|
| Dimensions | 25 1/4"W x 26"H x 14"D |
| Weight | 303 lbs. |
| Heating Capacity | App. 1,000 sq. ft. |
| Firebox Size | 1.8 cu. ft. |
| Max. Log Length | 18" |
| Door Opening Size | 16" x 8 1/2" |
| Window Opening | 15 3/4" x 8 1/2" |

Type of Fuel Wood
 Flue Size I.D. 6"
 Flue Hgt. to Top Exhaust 27 1/2"
 AC-G17 Glass 9 1/4" x 16 1/2"
 Ash Drawer Standard

Options:

AC-16 Room air blower
 AC-107 Brass lip trim (AC-107BN if Nickel)
 AC-108 Brass trim ring for door (AC-108BN if Nickel)
 AC-NCSHS Side heat shield (AC-NCSHSB for black)
 CA-12G Gold-plated leg
 CA-13G Gold-plated door

**Specifications for 30-NCP, 30-NCL & 30-NCG; 50-SNC30P, 50-SNC30L & 50-SNC30G;
 50-TNC30P, 50-TNC30L & 50-TNC30G**

Dimensions 23 1/4"W x 27 3/4"H x 24 1/2"D
 Weight 455 lbs.
 Heating Capacity App. 2,200 sq. ft.
 Firebox Size 3.5 cu. ft.
 Max. Log Length 20"
 Door Opening Size 11" x 15"
 Window Opening 10" x 13"
 Type of Fuel Wood
 Flue Size I.D. 6"
 Flue Hgt. to Top Exhaust 28 1/4"
 AC-G30 Glass 11 1/4" x 15 1/8"
 Ash Drawer Standard

Options:

AC-30 Room air blower
 AC-115 Brass lip trim (AC-115BN if Nickel)
 AC-116 Brass trim ring for door (AC-116BN if Nickel)
 AC-30SHS Side heat shield (AC-30SHSB for black)
 CA-12G Gold-plated leg
 CA-30G Gold-plated door

Specifications for 18-MH, 50-SHW15 & 50-TRW15 (Catalytic)

| | |
|--------------------------------|-------------------------|
| Dimensions | 22 ¼”W x 33” H x 19 ½”D |
| Weight | 350 lbs. |
| Heating Capacity | 1,000 sq. ft. |
| Max. Log Length | 16” |
| Door Opening Size | 12” x 13” |
| Window Opening | 8 ½” x 8 ½” |
| Flue Size I.D. | 6” |
| Flue Hgt. To Top Exhaust | 34 ¾” |
| AC-G9 Glass | 9” x 9” |
| Heat Shield (standard) | AC-PHS |
| Type of Fuel | Wood |
| Outside Air Pipe | 3” |

Options:

| | |
|--------------------------------------|--------------------------------------|
| Brass Lip Trim | AC-101-P (SH-101-P for Summers Heat) |
| Brass Window Trim | AC-106-P (SH-106-P for Summers Heat) |
| Blower System w/Rear Heat Shield ... | AC-20 (SH-20 for Summers Heat) |

Specifications for 28-3500, 50-SHW35 and 50-TRW35

| | |
|--------------------------------|---|
| Dimensions | 24 ½ ”W x 36” H x 30 ¼ ”D |
| Weight | Approx. 570 lbs. |
| Heating Capacity | Approx. 3,000 sq. ft. (when fed into existing ductwork) |
| Max. Log Length | 25” |
| Door Opening Size | 12 ½ ” x 11” |
| Window Opening | 8 ½” x 8 ½” |
| AC-G9 Glass | 9” x 9 ” |
| Blower Capacity | 850 cfm |
| Flue Size I.D. | 6” |
| Hot Air Outlet | 8” |
| Flue Hgt. To Top Exhaust | 36 ½ ” |
| Type of Fuel | Wood or Wood/Coal |

Options:

| | |
|-------------------------|--------------------------------------|
| Brass Window Trim | AC-106-P (SH-106-P for Summers Heat) |
|-------------------------|--------------------------------------|

Specifications for 18-TR/TRD, 50-SHW10/10D/10DL & 50-TRW10/10D

| | |
|--------------------------------|--------------------------------|
| Dimensions | 22 ¼”W x 33” H x 19 ½”D |
| Weight | Approx. 310 lbs. |
| Heating Capacity | 1,000 sq. ft. |
| Max. Log Length | 16” |
| Door Opening Size | 12” x 13” |
| Window Opening | 8 ½” x 8 ½” |
| Flue Size I.D. | 6” |
| Flue Hgt. To Top Exhaust | 34 ¾” |
| AC-G9 Glass | 9” x 9” |
| Ash Drawer | Standard on TRD and 10D models |
| Type of Fuel | Wood |

Options:

| | |
|--------------------------------------|---|
| Brass Lip Trim | AC-101-P (SH-101-P for Summers Heat) |
| Brass Window Trim | AC-106-P (SH-106-P for Summers Heat) |
| Rear and Side Heat Shield | AC-PHS (SH-HS10 for Summers Heat, AC-PHSB if black) |
| Blower System w/Rear Heat Shield ... | AC-20 (SH-20 for Summers Heat) |

Specifications for 24-ACD, 24-FC, 50-SHW24 and 50-SHW16/16L, and 50-TRW24 and 50-TRW16
(Catalytic)

| | |
|-------------------------------------|---|
| Dimensions | 21”W x 33” H x 24 ½”D |
| Weight | Approx. 495 lbs. |
| Heating Capacity | Approx. 1,800 sq. ft. (24-FC, 50-SHW16/16L and 50-TRW16) Approx. 2,000 sq. ft. (24-ACD, 50-SHW24 and 50-TRW24) |
| Max. Log Length | 20” |
| Door Opening Size | 12” x 13” |
| Window Opening | 8 ½” x 8 ½” |
| Flue Size I.D. | 6” |
| Flue Hgt. To Top Exhaust | 36” |
| Flue Hgt. To Rear Exh. Center | 26 ½” |
| AC-G9 Glass | 9” x 9” |
| AC-16 Blower | Standard on 24-ACD, 50-SHW24 and 50-TRW24 |
| Type of Fuel | Wood |

Options:

| | |
|---------------------------------|--|
| Brass Lip Trim | AC-102 (SH-102 for Summers Heat) |
| Brass Window Trim | AC-106-P (SH-106-P for Summers Heat) |
| Rear and Side Heat Shield | AC-AHS (SH-HS22 for Summers Heat)-for models with blower only; otherwise AC-FHS for radiant models (AC-FHSB if black) |

Specifications for 24-ICD, 50-SHW25 and 50-TRW25 (Catalytic)

| | |
|-------------------------------------|------------------------|
| Dimensions | 26"W x 33" H x 24 ¾ "D |
| Weight | Approx. 570 lbs. |
| Heating Capacity | Approx. 2,500 sq. ft. |
| Max. Log Length | 20" |
| Door Opening Size | 9" x 16 ½ " |
| Window Opening | 7 ½" x 13 ½" |
| Flue Size I.D. | 6" |
| Flue Hgt. To Top Exhaust | 35 ¾ " |
| Flue Hgt. To Rear Exh. Center | 26 ½" |
| AC-G8 Glass | 8 ½ " x 13 ¾ " |
| AC-16 Blower | Standard |
| Type of Fuel | Wood |

Options:

| | |
|---------------------------------|-----------------------------------|
| Brass Lip Trim | AC-101 (SH-101 for Summers Heat) |
| Rear and Side Heat Shield | AC-IHS (SH-HS25 for Summers Heat) |

Specifications for 24-JC, 50-SHW20 and 50-TRW20 (Catalytic)

(NOTE: for masonry installation only)

| | |
|--|--------------------------|
| Dimensions | 26"W x 23 ¼ "H x 25 "D |
| Weight | 580 lbs.(with backplate) |
| Heating Capacity | Approx. 2,000 sq. ft. |
| Max Log Length | 20" |
| Door Opening Size | 9" x 16 ½" |
| Window Opening | 7 ½" x 13 ½" |
| AC-17 Blower | Standard |
| AC-G8 Glass | 8 ½ " x 13 ¾ " |
| Flue Size I.D. | 8" |
| Flue Hgt. to Top Exhaust | 23 ½" |
| Hearth Size Required | 14" |
| Min. Fireplace Opening | 28"W x 24"H x 16"D |
| Fireplace Cover (comes standard) | 32" x 46" |
| Type of Fuel | Wood |

Options:

| | |
|------------------------------------|----------------------------------|
| Brass Backplate and Lip Trim | AC-104 (SH-104 for Summers Heat) |
|------------------------------------|----------------------------------|

PELLET STOVES

Specifications for 25-PAF, 55-SHP25 and 55-TRP25

| | |
|-------------------------|------------------------|
| Dimensions | 23"W x 38"H x 25 "D |
| Weight | 370 lbs. |
| Heating Capacity | Approx. 2,500 sq. ft. |
| Hopper Capacity | 80 lbs. |
| Door Opening Size | 12" x 13" |
| Window Opening | 8 ½" x 8 ½" |
| Hot air outlet | 6" |
| Flue Size I.D. | 3" pellet rear vent |
| Type of Fuel | Wood pellets |
| AC-G9 Glass | 9" x 9" |
| Blower Capacity | 850 cfm variable speed |
| Ash Drawer | Standard |

Options:

| | |
|----------------------------------|--------------------------------------|
| Brass Lip Trim | AC-103 |
| Brass Window Trim | AC-106-P (SH-106-P for Summers Heat) |
| Wall Thermostat | GU-1E30-914 |
| Simpson 3" Pellet Vent Kit | AC-3000 |

Specifications for 25-PDV, 55-SHP22/22L and 55-TRP22, American Heritage

| | |
|---|---------------------------------------|
| Dimensions | 28 ½ "W x 30"H x 28 ½"D |
| Weight | 375 lbs. |
| Heating Capacity | Approx. 2,200 sq. ft. |
| Hopper Capacity | 60 lbs. |
| Window Opening | 8 ½" x 8 ½" |
| Height - floor to center of exhaust | approx. 13 ½" |
| AC-G9 Glass | 9" x 9" |
| Flue Size I.D. | 3" pellet rear vent |
| Type of Fuel | Wood pellets |
| Blower Capacity | 250 cfm variable speed |
| AC-106-P | Window trim (or AC-106-PBN if Nickel) |

Options:

| | |
|----------------------------------|--|
| Brass Lip Trim | AC-103 (AC-103BN for Nickel) |
| Wall Thermostat | GU-1E30-914 / Remote Thermostat....AC-3001 |
| Simpson 3" Pellet Vent Kit | AC-3000 (AC-3100 for 4000 ft.+) |
| Outside Air Kit | PU-OAK |

Specifications for 25-PI, 55-SHP20 and 55-TRP20

(NOTE: for masonry installation only)

| | |
|------------------------------|---------------------------------------|
| Dimensions | 27 ½ ”W x 22”H x 28 ½”D |
| Weight | 410 lbs.(with backplate) |
| Heating Capacity | Approx. 2,000 sq. ft. |
| Hopper Capacity | 50 lbs. |
| Window Opening | 8 ½” x 8 ½” |
| AC-G9 Glass | 9” x 9” |
| Flue Size I.D. | 3” pellet rear vent |
| Hearth size required | 12” |
| Min. fireplace opening | 28”W x 22 ¼ “H x 17”D |
| Fireplace Cover | 32” x 46” (comes standard) |
| Type of Fuel | Wood pellets |
| Blower Capacity | 250 cfm variable speed |
| AC-106-P | Window trim (or AC-106-PBN if Nickel) |

Options:

| | |
|------------------------------------|--|
| Brass Lip and Backplate Trim | AC-104 (SH-104 for Summers Heat) |
| Wall Thermostat | GU-1E30-914 / Remote Thermostat....AC-3001 |

Specifications for 25-PDVC, 55-SHP10/10L and 55-TRP10, American Standard

| | |
|---|------------------------|
| Dimensions | 23 ”W x 28”H x 21”D |
| Weight | 290 lbs. |
| Heating Capacity | Approx. 1,500 sq. ft. |
| Hopper Capacity | 40 lbs. |
| Window Opening | 8 ½” x 8 ½” |
| Height - floor to center of exhaust | approx. 13 ½” |
| AC-G9 Glass | 9” x 9” |
| Flue Size I.D. | 3” pellet rear vent |
| Type of Fuel | Wood pellets |
| Blower Capacity | 140 cfm variable speed |

Options:

| | |
|----------------------------------|--|
| Brass Lip Trim | AC-103 (AC-103BN for Nickel) |
| Wall Thermostat | GU-1E30-914 / Remote Thermostat....AC-3001 |
| Simpson 3” Pellet Vent Kit | AC-3000 (AC-3100 for 4000 ft.+) |
| Outside Air Kit | PU-OAK |

GAS STOVES

Specifications for 26-GU, 60-SHU and 60-TRU

| | |
|--------------------------------------|---|
| Dimensions | 27 ½ ”W x 27”H x 17 ½”D |
| Weight | 72 lbs. |
| Type of fuel | Choose Natural (“NG”) or Propane (“LP”) Gas model |
| Color | Matte Black |
| Optional Blower System | AC-26BA blower |
| Natural Gas Model BTU Input | App. 20,000 – 34,500 BTU/hr. |
| Liquid Propane Model BTU Input | App. 20,000 – 30,000 BTU/hr. |
| Efficiency Rating | 99% |
| Venting | Vent-free |

Options:

| | |
|--------------|---------|
| Blower | AC-26BA |
|--------------|---------|

Specifications for 26-GUH, 60-SHUH and 60-TRUH

| | |
|--------------------------------------|---|
| Dimensions | 27 ½ ”W x 27”H x 17 ½”D |
| Weight | 78 lbs. |
| Type of fuel | Choose Natural or Propane Gas model |
| Color | Hunter Green |
| Optional Blower System | AC-26BA blower |
| Optional Fireplace Cover | 30” x 40”, for hearth application |
| Optional Fireplace Cover Trim | AC-104-G brass backplate trim (SH-104-G for Summers Heat) |
| Natural Gas Model BTU Input | App. 20,000 – 34,500 BTU/hr. |
| Liquid Propane Model BTU Input | App. 20,000 – 30,000 BTU/hr. |
| Efficiency Rating | 99% |
| Venting | Vent-free |

Options:

| | |
|----------------------------|---|
| Blower | AC-26BA |
| Fireplace Cover | STB-UV (SHTB-UV for Summers Heat)-for hearth applications |
| Brass Backplate Trim | AC-104-G (SH-104-G for Summers Heat) — fits STB-UV (SHTB-UV for Summers Heat) cover plate |

Specifications for 26-GBV, 60-SHBV and 60-TRBV

| | |
|--|---|
| Dimensions | 27 ½ ”W x 27”H x 17 ½”D |
| Weight | 185 lbs. |
| Type of fuel | Choose Natural (“NG”) or Propane (“LP”) Gas model |
| Color | Charcoal Gray |
| Standard Blower System | AC-26BA blower |
| Flue Size I.D. | 4” Approved B-Vent |
| Flue Hgt. to Top Exhaust | 30” |
| Flue Hgt. to Center of Rear Exhaust | 24” |
| Natural Gas Model BTU Input | App. 22,500 – 32,000 BTU/hr. (77.9% efficiency) |
| Liquid Propane Model BTU Input | App. 18,600 – 33,200 BTU/hr. (81.7% efficiency) |

COAL STOVES

Specifications for 27-C2000, 50-SHWC2 and 50-TRWC2

| | |
|-------------------------------------|---|
| Dimensions | 24 ½ ”W x 36” H x 15 ½ ”D |
| Weight | Approx. 408 lbs. |
| Heating Capacity | Approx. 2,000 sq. ft. |
| Coal Size | Over ½” |
| Door Opening Size | 12 ½ ” x 11 ” |
| Window Opening | 8 ½” x 8 ½” |
| AC-G9 Glass | 9” x 9” |
| Flue Size I.D. | 6” |
| Flue Hgt. To Top Exhaust | 38 ½ ” |
| Flue Hgt. To Rear Exh. Center | 31” |
| Type of Fuel | Coal only (U.S.A.); Wood or Coal (Canada) |

Options:

| | |
|-------------------------|--------------------------------------|
| Brass Window Trim | AC-106-P (SH-106-P for Summers Heat) |
|-------------------------|--------------------------------------|

Specifications for 27-C3000, 50-SHWC3 and 50-TRWC3

| | |
|-------------------------------------|---|
| Dimensions | 28 ¼ ”W x 36” H x 23 ”D |
| Weight | Approx. 652 lbs. |
| Heating Capacity | Approx. 2,600 – 2,800 sq. ft. |
| Coal Size | Over ½” |
| Door Opening Size | 9 ” x 16 ½ ” |
| Window Opening | 8 ½” x 14” |
| AC-G8 Glass | 8 ½ ” x 13 ¾ ” |
| Flue Size I.D. | 6” |
| Flue Hgt. To Top Exhaust | 36 ” |
| Flue Hgt. To Rear Exh. Center | 31” |
| Type of Fuel | Coal only (U.S.A.); Wood or Coal (Canada) |
| Standard | AC-16 Blower |
| Standard | Brass Door and Window Trim |